

How to connect the DONMET 132P cutting torch to gas cylinders.

The following are used as examples:

Pressure regulator RO-200-2 DM mini G3/4 – G1/4

Pressure regulator RP-25 DM mini W21.8x1/14 LH – G3/8LH

Other models of pressure regulators with different outlet connection sizes may be used.

Use a 9 mm hose for the G3/8 thread and a 6 mm hose for the G1/4 thread.

The combination nipples on the DONMET 132P cutting torch are compatible with 6 and 9 mm diameter hoses..

Cutting torch "DONMET" 132P MICRO, complete
(cutter + 1.5 m O₂/gas hoses 3.2 mm + combination nipples + clamps)
Order №. 132.000.01

GOX hose, 6 mm,
20 bar, L=3-5 m

For example –
Pressure regulator
RO-200-2 DM mini
G3/4 – G1/4
Order №. 006.000.10

Small nipple 6E
Order №. 145.002.01

6 mm compression
sleeve clamp
Order №. 903.100.01

1/4" E Socket Wrench
Order №. 145.004.00

9 mm compression
sleeve clamp
Order №. 903.200.01

6 mm compression
sleeve clamp
Order №. 903.100.01

9 mm compression
sleeve clamp
Order №. 903.200.01

Large nipple 8E
Order №. 145.003.02

3/8 LH E Socket Wrench
Order №. 145.005.01

GAC hose 9 mm,
20 bar, L=3-5 m

For example -
Pressure regulator
RP-25 DM mini
W21.8x1/14 LH – G3/8LH
Order №. 008.000.10

